

## Seriya T4 V/N/F



### T4000 V/N/F modeli

	T4020V	T4030V/N/F	T4040V/N/F	T4050V/N/F	T4060V/N/F
Motor New Holland NEF CEGR tehnologija	NEF Tier III				
Broj cilindara/zapremina cm <sup>3</sup>	4/3200	4/3200	4/3200	4/4500	4/4500
Nominalna snaga ISO 14396 (kW/hp)	48/65	57/78	65/88	71/97	78/106
<b>Transmisija</b>					
Shuttle Command (40 km)	16x16	16x16	16x16	16x16	16x16
Power Shuttle (40km)	16x16	16x16	16x16	16x16	16x16
<b>Hidraulika</b>					
Maksimalna podizna moć na kuglama (kg)	2600	2600	2600	2600	2600
Kapacitet uljne pumpe (l/min)	49	49	49	49	49
Radijus okretanja/SuperSteer (mm)	3400-	3400-2960	3400-2960	3400-3050	3400-3050
Osnovna težina (bez tegova)	2710	2710-4300	2710-4300	2790-4300	2790-4300

## Seriya TT



### TT model

### TT45

Motor New Holland	Tier II
Broj cilindara/zapremina cm <sup>3</sup>	3/2500
Nominalna snaga ISO 14396 (kW/hp)	35/47
<b>Transmisija</b>	
Max. brzina km/h	30
Mechanical 2WD	8x2
PTO	540
Max. širina (mm)	1380
Osnovna težina (bez tegova) (kg)	1460



AGROGLOBE



## TRAKTORI

## Seriya T8



### T8 TIER IV modeli

	T8.300	T8.330	T8.360	T8.390
Motor FPT ECOBlue™ SCR tehnologija	4 ventila po cilindru /CURSOR9/TIER4A			
Broj cilindara/zapremina	6/8700	6/8700	6/8700	6/8700
Maksimalna EPM snaga ISO 14396 (kW/hp)	219/298	241/327	263/357	286/389
Nominalna snaga ISO 14396 (kW/hp)	189/257	209/284	229/311	250/340
<b>Transmisija IntelliShift™</b>				
Ultra Command Full PowerShift (40km/h ECO ili 50km/h)	19x4	19x4	19x4	19x4
Ultra Command Full PowerShift(40km/h ECO sa puzajućim brzinama)	23x6	23x6	23x6	23x6
<b>Hidraulika</b>				
Maksimalna podizna moć na kuglama (kg)	9130	9130	10200	10200
Kapacitet uljne pumpe standard /MegaFlow™ (l/min)	161/274	161/274	161/274	161/274
Osnovna težina (bez tegova) kg	11010	11315	11315	11315
Ukupna težina (maksimalno opterećen)	17500	18000	18000	18000



AGROGLOBE

Sentandrejski put 165, Novi Sad, www.agroglobe.rs

### Severna Bačka i severni Banat

Ištvan Štajer, komercijalista  
064/871 34 66  
istvan.stajer@agroglobe.rs

### Srednja i južna Bačka

Srdan Vučenov, komercijalista  
064/871 34 95  
srdjan.vucenov@agroglobe.rs

### Srednji i južni Banat

Dalibor Popović, komercijalista  
064/871 34 94  
dalibor.popovic@agroglobe.rs

### Srem i centralna Srbija

Karlo Hrubenja, komercijalista  
064/871 34 57  
karlo.hrubenja@agroglobe.rs

### SERVIS

tel. 021/21 55 931  
fax 021/21 55 932

### Rezervni delovi

Dušan Milovanović  
064/871 34 05  
dusan.milovanovic@agroglobe.rs



## Seriya T7



### Model Klasik i SideWinder II™

	T7.210	T7.260
Motor FPT ECOBlue™ SCR tehnologija	6/6728 Tier 4A	
Broj cilindara/zapremina	6/6728 Tier 4A	
Maksimalna EPM snaga ISO 14396 (kW/hp)	156/212	191/260
Nominalna snaga ISO 14396 (kW/hp)	121/165	158/215
<b>Transmisija</b>		
Range Command™ IntelliShift™	18x6	
Power Command Ful PowerShift (40 km/h ECO ili 50 km/h)		18x6
<b>Hidraulika</b>		
Kapacitet uljne pumpe standard /MegaFlow™ (l/min)	113/125	120/150
Maksimalna podizna moć na kuglama (kg)	8257	10450
Osnovna težina (bez tegova) kg	5950	6950

## Seriya T6



### T6 TIER IV modeli

	T6.150	T6.175
Motor NEF ECOBlue™ SCR tehnologija	Tier 4A	
Broj cilindara/zapremina	4/4485	6/6728
Maksimalna EPM snaga ISO 14396 (kW/hp)	113/154	129/175
Nominalna snaga ISO 14396 (kW/hp)	89/121	103/140
<b>Transmisija</b>		
Dual Command(1,64-40km/h)	24x24	24x24
Electro Command	16x6	16x6
<b>Hidraulika</b>		
Kapacitet uljne pumpe standard /CCLS (l/min)	80/113	80/113
Maksimalna podizna moć na kuglama (kg)	7864	7864
Osnovna težina (bez tegova) kg	5490	5610

## Seriya T5



### T5 modeli

	T5.95	T5.105	T5.115
Motor FPT ECOBlue™ CEGR tehnologija	NEF Tier 4A		
Broj cilindara/zapremina	4/3400	4/3400	4/3400
Nominalna snaga ISO 14396 (kW/hp)	73/99	79/107	84/114
<b>Transmisija</b>			
Powershuttle (40km/h)	12x12	12x12	12x12
Dual Command™ (40km/h)	24x24	24x24	24x24
<b>Hidraulika</b>			
Maksimalna podizna moć na kuglama (kg)	5420	5420	5420
Kapacitet uljne pumpe/MegaFlow™ (l/min)	65/84	65/84	65/84
<b>Osnovna težina (bez tegova)</b>	4250	4250	4250

## Seriya TD5



### TD5 modeli

	TD5.65	TD5.75	TD5.85	TD5.95	TD5.105	T5.115
Motor New Holland NEF CEGR tehnologija	NEF Tier III					
Broj cilindara/zapremina cm <sup>3</sup>	3/2930	3/2930	4/3200	4/4485	4/4485	4/4485
Nominalna snaga ISO 14396 (kW/hp)	48/65	53/72	60/82	70/95	78/106	83/113
<b>Transmisija</b>						
SinchoShuttle (40 km)	12x12	12x12	12x12	12x12		
PowerShuttle (40km)			12x12	12x12	12x12	12x12
<b>Hidraulika</b>						
Maksimalna podizna moć na kuglama (kg)	3000	3000	3565	3565	3565	3565
Kapacitet uljne pumpe (l/min)	36	36	50	50	50	50
Osnovna težina (bez tegova)	3080	3080	3700	3900	3900	3900