



Modeli	TC5050	TC5060	TC5070	TC5080
	Stari dizajn		Novi dizajn	
Motor/zapremina/ubrizationje	FPT/6,8 l/Mech	FPT/6,8 l/Mech	FPT/6,8 l/Common rail SCR ECOBlue	
Nom. Snaga ECE R120 (2100 obr) (kW/hp)	125/170	125/170	155/210	175/238
Max. Snaga ECE R120 (2000 obr) (kW/hp)	129/175	129/175	167/227	190/258
Radni zahvat kose (m)	3.96	4.57	5.18	5.18
Tehnologija vršaja i separacije	2 bubnja	2 bubnja	2 ili 3 bubnja	3 bubnja
Prečnik bubnja/širina (m)	0,607/1,04	0,607/1,30	0,607/1,30	0,607/1,30
RotoSeparator	-	Opcija	Po izboru	Standard
Ukupna Površina Separacije (m ²)	0.99	1,186/1,82	1,186/1,82	1.82
Broj Slamotresa	4		5	
Površina slamotresa (m ²)	4.41	5,51/4,68	5,51/4,68	5.51
Površina sita (m ²)	3.27		4.3	
Kapacitet bunkera (l)	4000	5200		6400
Transmisija	Hidro		Hidro	
Kukuruzni adapter	4	4 ili 5	5 ili 6	6



AGROGLOBE

Sentandrejski put 165, Novi Sad, www.agroglobe.rs

Severna Bačka i severni Banat
Ištvan Štajer, komercijalista
064/871 34 66

Srednja i južna Bačka
Srđan Vučenov, komercijalista
064/871 34 95

Srednji i južni Banat
Dalibor Popović, komercijalista
064/871 34 94

Srem i centralna Srbija
Karlo Hrubenja, komercijalista
064/871 34 57

SERVIS
064/ 871 34 90

Rezervni delovi
Dušan Milovanović
064/871 34 05



AGROGLOBE



KOMBAJNI

Serija CR



Modeli	CR8070	CR9070	CR9090
Motor	FPT/8,7 l/Cursor 9, SCR ECOBlue	FPT/10,2 l/Cursor 10, SCR ECOBlue	FPT/12,9 l/Cursor 13, SCR ECOBlue
Nom. Snaga ISO 14396 (kW/hp)	300/408	330/449	390/530
Max. Snaga ISO 14396 (kW/hp)	330/449	360/490	420/571
Radni zahvat kose (m)	7.32	7,32-10,67	
Tehnologija vršaja i separacije	TWIN ROTOR™ tehnologija		
Prečnik Rotora (mm)	425	550	
Dužina rotora (m)	2.64	2.64	
Opti-Clean™ system	standard	standard	
Totalna površina čišćenja (m ²)	5.4	6.5	
Kapacitet bunkera (l)	9500	11500	12500

Seriya CX 8000



Modeli	CX7090 Elevation	CX8070 Elevation	CX8090 Elevation
Motor	FPT/8,7 I/Cursor 9, SCR ECOBlue		FPT/10,2 I/Cursor 10, SCR ECOBlue
NOM. Snaga ISO14396 (kW/hp)	240/326	240/326	330/449
MAX. Snaga ISO14396 (kW/hp)	270/367	270/367	360/490
Radni zahvat kose (m)	6.1	6,1-7,32	7,32-9,15
Tehnologija vršaja i separacije	4 bubnja		
Prečnik bubnja/Širina (m)	0,75/1,30	0,75/1,56	
Ukupna Površina Separacije (m ²)	2.11	2.54	
Broj Slamotresa	5	6	
Površina slamotresa (m ²)	4.94	5.93	
Površina sita (m ²)	5.4	6.5	
Kapacitet bunkera (l)	10000	9500	11500

Seriya CX 6000 5000



Modeli	CX5080	CX6090
Motor	FPT/6,8 I/Common rail SCR ECOBlue	FPT/8,7 I/Cursor 9, SCR ECOBlue
NOM. Snaga ISO14396 (kW/hp)	175/238	220/300
MAX. Snaga ISO14396 (kW/hp)	190/258	245/333
Radni zahvat kose (m)	5.18	6.1
Tehnologija vršaja i separacije	3 bubnja	3 bubnja
Prečnik bubnja/Širina (m)	606	606
RotoSeparator	standard	
Ukupna Površina Separacije (m ²)	1.98	2.38
Broj Slamotresa	5	6
Površina slamotresa (m ²)	6.03	7.22
Površina sita (m ²)	5.38	6.45
Kapacitet bunkera (l)	7000	9300

Seriya RB



Model	Roll Baler 125	Roll Belt 150	Roll Belt 180
Prečnik Bale (m)	125	0,9-1,5	0,9-1,8
Širina Bale(m)	120	1.2	1.2
Radni zahvat Pickup-a	2.1	1,5/1,8	1,5/1,8
Tip Pickup-a	2.1	Fork/rotor	Fork/rotor
CropCutter™ sistem (br. Noževa)	-	15	15
Tip Komore	fiksna	Roll-Belt™/pr.	Roll-Belt™/pr.
snaga kardana (KS): roto feder/cutter	65-70	70/80	70/80
Vezivanje bale	mreža	Kanap/mreža	Kanap/mreža
Duckbill sistem	-	EdgeWrap™	EdgeWrap™
Konzerviranje	-	opcija	opcija



Seriya BB



Model	BigBaler 870			BB9090	
	Standard	Paker sekač	Roto sekač	Standard	Roto sekač
Minimalna snaga na kardanu (kw/KS)	75/102	80/108	90/122	112/150	135/180
Širina bale (cm)	80	80	80	120	120
Visina bale (cm)	70	70	70	130	139
Max. Dužina bale (cm)	260	260	260	275	275
Radni Zahvat (m)	1.97	1.98	1.98	2.34	2.34
Brzina Klipa (Udarac/min)	48	48	48	33	33
CropCutter™ sistem (br. noževa max.)	-	6	9 ili 19	-	15 ili 29
Uvodnik - Packer sistem	2 viljuške sa 6 opruga	3 viljuške sa 6 opruga	"W" Rotor širine 800 mm	3 viljuške sa 6 opruga	"W" Rotor širine 1200 mm



Seriya FR



Modeli	FR450	FR850
Motor New Holland NEF CEGR tehnologija	FPT/8,7 I/Cursor 9, SCR ECOBlue	FPT Vector 20 (20 l)
Broj Cilindara/Zapremina cm ³	300/409	565/768
Nominalna snaga ISO 14396 (kW/hp)	330/449	606/824
Transmisija	standard	
ShuttleCommand (40 km)	HydroLoc™ pogon	
PowerShuttle (40km)	860	860
Hidraulika	standard	
Maksimalna podizna moc na kuglama (kg)	900/710	900/710
Kapacitet uljne pumpe (l/min)	750/200	750/250
Radius okretanja/SuperSteer (mm)	standard	
Osnovna težina (bez tegova)	750/525	750/525

