

Serija T4 V/N/F



T4 V/N/F modeli	T4.65 V	T4.75 V/N/F	T4.85 V/N/F	T4.95 V/N/F	T4.105 V/N/F
Motor FPT	NEF Tier III				
Broj Cilindara/Zapremina cm ³	4/3200	4/3200	4/3200	4/4500	4/4500
Nominalna snaga ISO 14396 (kW/hp)	48/65	57/78	65/88	71/97	78/106
Transmisija					
ShuttleCommand (40 km)	16x16	16x16	16x16	16x16	16x16
PowerShuttle (40km)	16x16	16x16	16x16	16x16	16x16
Hidraulika					
Maksimalna podizna moc na kuglama (kg)	2600	2600	2600	2600	2600
Kapacitet uljne pumpe (l/min)	49	49	49	49	49
Min.radijus okretanja (mm)	3400	3400-2960	3400-2960	3440-3050	3440-3050
Osnovna težina (bez tegova)	2710	2710-4300	2710-4300	2790-4300	2790-4300

Serija TT



TT model	TT45
Motor New Holland	Tier II
Broj cilindara/zapremina cm ³	3/2500
Nominalna snaga ISO 14396 (kW/hp)	35/47
Transmisija	
Max. brzina km/h	30
Mechanical 2WD	8x2
PTO	540
Max.širina (mm)	1380
Osnovna težina (bez tegova) (kg)	1460



AGROGLOBE

Sentandrejski put 165, Novi Sad, www.agroglobe.rs

Severna Bačka i severni Banat

Ištvan Štajer, komercijalista
064/871 34 66
istvan.stajer@agroglobe.rs

Srednja i južna Bačka

Srdan Vučenov, komercijalista
064/871 34 95
srdjan.vucenov@agroglobe.rs

Srednji i južni Banat

Dalibor Popović, komercijalista
064/871 34 94
dalibor.popovic@agroglobe.rs

Srem i centralna Srbija

Karlo Hrubenja, komercijalista
064/871 34 57
karlo.hrubenja@agroglobe.rs

SERVIS

064/871 34 60, 021/ 21 55 932
servis@agroglobe.rs

Rezervni delovi

Dušan Milovanović
064/871 34 05, 021/21 559 30
dusan.milovanovic@agroglobe.rs



AGROGLOBE



TRAKTORI

Serija T8



T8 modeli - TIER 4B	T8.320	T8.350	T8.380	T8.410
Motor FPT ECOBlue™ Hi-eSCR, turbo sitem	CURSOR 9, WT			
broj cilindara/zapremina	6 / 8700 Tier 4B			
Maksimalna EPM snaga ISO 14396 (kW/hp)	235 / 320	258 / 351	281 / 381	301 / 409
Nominalna snaga ISO 14396 (kW/hp)	184 / 250	206 / 280	229 / 311	250 / 340
Maksimalna snaga ISO 14396 (kW/hp)	209 / 284	232 / 315	255 / 347	275 / 374
Transmisija				
Ultra Command Full PowerShift (40 ECO ili 50 km/h)	19 x 6	19 x 6	19 x 6	19 x 6
Hidraulika				
Kapacitet uljne pumpe standard/MegaFlow™ (l/min)	166 / 282	166 / 282	166 / 282	166 / 282
Maksimalna podizna moc na kuglama (kg)	8843	8843	9705	10927
Medjuosovinsko rastojanje (mm)	3450	3450	3450	3450
Osnovna tezina - bez tegova (kg)	11235	11360	11360	11440

Seriya T7



Model Klasik I SideWinder II	T6080	T7060	T7.210	T7.260	T7.290
Motor.....					
Broj cilindara....	6 / 6728 Tier III		6/6728 Tier 4A	6/6728 Tier 4B	6/6728 Tier 4B
Maksimalna EPM snaga....	142 / 193	178 / 242	156 / 212	191 / 260	212 / 288
Nominalna Snaga....	114 / 155	157 / 213	121 / 165	162 / 220	199 / 271
Transmisija					
Range....	18 x 6		18 x 6		AutoCommand
Power....		18 x 6		18 x 6	CVT
Hidraulika					
Kapacitet uljne pumpe....	113 / 125	120 / 150	113 / 125	120 / 150	165 / 220
Maksimalna podizna....	8257	10463	8257	10463	11058
Osnovna težina....	5650	6850	5950	7300	10500

Seriya T6



T6 TIER IV modeli	T6.150	T6.175
Motor NEF ECOBlue™ SCR tehnologija	Tier 4A	
Broj cilindara/zapremina	4/4485	6/6728
Maksimalna EPM snaga ISO 14396 (kW/hp)	113/154	129/175
Nominalna snaga ISO 14396 (kW/hp)	89/121	103/140
Transmisija		
Dual Command(1,64-40km/h)	24x24	24x24
Electro Command	16x6	16x6
Hidraulika		
Kapacitet uljne pumpe standard /CCLS (l/min)	80/113	80/113
Maksimalna podizna moć na kuglama (kg)	7864	7864
Osnovna težina (bez tegova) kg	5490	5610

Seriya T5



T5 modeli	T5.95	T5.105	T5.115
Motor FPT ECOBlue™ CEGR tehnologija	NEF Tier 4A		
Broj cilindara/zapremina	4/3400	4/3400	4/3400
Nominalna snaga ISO 14396 (kW/hp)	73/99	79/107	84/114
Transmisija			
Powershuttle (40km/h)	12x12	12x12	12x12
Dual Command™ (40km/h)	24x24	24x24	24x24
Hidraulika			
Maksimalna podizna moć na kuglama (kg)	5420	5420	5420
Kapacitet uljne pumpe/MegaFlow™ (l/min)	65/84	65/84	65/84
Osnovna težina (bez tegova)	4250	4250	4250

Seriya TD5



TD5 modeli	TD5.75	TD5.90	TD5.95	TD5.110	TD5.115
Motor, kvalitet izduvnih gasova	S8000 - Turbo / Intercooler, Tier III	S8000 - Turbo / Intercooler, Tier III	FPT F5C, common rail, Tier 4A	S8000 - Turbo / Intercooler, Tier III	FPT F5C, common rail, Tier 4A
Broj cilindara/zapremina ccm ³	4 / 3900	4 / 3900	4 / 3400	4 / 3900	4 / 3400
Nominalna snaga ISO 14396 (kW/hp)	55/75	64/88	73/99	81/110	84/114
Transmisija					
SinchoShuttle (40 km)	12x12	-	-	-	-
PowerShuttle (40km)	-	12x12	12x12	12x12	12x12
Hidraulika					
Maksimalna podizna moć na kuglama (kg)	3565	3565	4700	4500	4700
Kapacitet uljne pumpe (lit.)	51	51	63	51	63
Osnovna težina (bez tegova)	3600	3700	3740	3900	3740